

30P COMPRESSOR

SINGLE-STAGE PISTON SERIES 30 CFM



Compressor Specifications

Output Capacity:	30 cfm @ 100 psi
Hydraulic Req:	11 gpm @ 1850 psi
Cylinders:	4-cylinder, single-stage
Max Pressure:	150 psi
Weight:	235 lbs.

The 30P is manufactured for reliability and longevity. A direct-drive, with no belts to break or adjust, it provides a quick 30 CFM @ 100 PSI. Built around a heavy ductile iron balanced crankshaft with heavy-duty journal bushings and micro-honed connecting rods, it provides smooth operation and long life.

Air tanks and/or a hydraulic reservoirs are available upon request.

30P SINGLE-STAGE PISTON SERIES 30 CFM

Durability Standard

- Cast Iron Crankcase Casting
- Cast Aluminum Cylinder Head
- High Temperature Precision Pistons
- Stainless Steel Reed Valves
- Heavy Duty Journal Bushings
- Pulsation Manifold
- Heavy Ductile Iron Crankshaft
- Micro-honed Connecting Rods
- Tapered Roller Bearings
- Pressure Lubricated System
- Oil Pressure Gauge

Ease of Use

- Canister Air Filters for easy replacement
- Oil dipstick for easy visual check
- Bulkhead fittings for quick hook-up
- Simple and inexpensive to maintain

Directly driven off of hydraulic motor means no broken belts, ever. The Compressor includes a high capacity hydraulic cooler and fan for cooler operation. One piece cylinder and head design mean that there are no head gaskets to fail.

*Specifications may change without notification.

Your Contact:

Telephone: 800-392-3015
E-mail: sales@americaneagleacc.com
www.americaneagleacc.com

Designed & Manufactured in the U.S.A.
Copyright © 2016 American Eagle Accessories Group